## Application for Approval of Boat Storage Naples Bay Yacht Stowage Condominium Association, Inc. ("NBYSCAI")

Any party that is to store a boat at Naples Bay Yacht Stowage must fill out an application to submit to the Board of Directors of the Association for approval along with an application fee of \$100.00 payable to Naples Bay Yacht Stowage. The Buyer/Tenant has received and agrees to abide by NBYSCAI "Rules and Regulations". A copy of the NBYSCAI Rules and Regulations signed by the Applicant must be attached to this application.

Please fill out the following information and submit it to the Association office.

Buver/Tenant: Address: Telephone Number: Other Family, Friends and Authorized Users 'of Vessel: Email address: \_\_\_\_\_\_Slip Number: \_\_\_\_\_ **Boat Specifications:** \_\_\_\_ Boat Model: \_\_\_\_\_ Year: \_\_\_\_ Boat Make: Length Overall: \_\_\_\_\_ Includes bow pulpits, swim platforms, anchor extensions, engines, etc. Measured after the boat has been placed in the storage rack to top of highest point. Height: Includes T-tops, Radar arches, hardtop, canvas extensions, anything non-collapsible, etc. Overall Weight: \_\_\_\_\_ When fuel and water tanks are at full (capacity X 7 lbs.), plus 200 lbs on average for personal gear, plus the weight of the boat. Beam (Width): Measured from railings or any other protruding object from the sides of the boat. The above measurements must be used to determine the correct size dry storage slip required for your boat. It will be necessary for all Applicants to obtain exact measurements prior to purchasing a dry slip. Vessel owner is required to provide NBYS with accurate vessel measurements. Any misrepresentation or failure to provide accurate vessel measurements by the boat owner will void the application for boat storage. (A Certificate of Insurance must be mailed or faxed directly from your insurance carrier to the NBYSAI manager prior to the boat's placement in boathouse). Any other pertinent information: Note: All internal engine compartments must be equipped with a fixed fire protection /flame arrestor system. NBYSCAI requires the Applicant to maintain minimum clearances between the boat and the boat storage building structure as follows: When the boat is placed on the storage rack in the dry slip, the boat must have minimum clearances of six inches (6") from the width of the boat on each side, twelve inches (12") from the height of the boat, and twenty-four inches (24") from the length (12" from the front of the boat and 12" from the rear of the boat) of the boat in order for the forklift to safely operate and maneuver the boat in to and out of the dry slip. If at any time it is determined that there is a boat in any dry slip that does not meet the minimum clearance requirements set forth above, the boat must immediately be removed at the expense of the owner or renter. NBYSCAI employees or representatives are not responsible for the measurement of your vessel or for any discrepancy resulting from Purchaser or Renter's failure to measure properly. The owner or renter may not rely on any representation from an NBYSCAI employee or representative that deviates from the above minimum clearance requirements. Buyer's Signature: Date: \_\_\_\_\_ Date application received: Approved: \_\_\_\_\_NBYS Manager, on behalf of the Board of Directors Print Name: